

AL™
U N D

ably
less than
pound
that
e mixing.
pre-
the fitting

pound
entire
uctors.
packing
rs is
ore
r in five?
save an
ling fitting



COOPER Crouse-Hinds
PO Box 4999
Syracuse, NY 13221



COOPER Crouse-Hinds

Cooper Ex. 1010

DOCKET
A L A R M

Find authenticated court documents without watermarks at docketalarm.com.

Chico® X Fiber:

- used in vertical applications to form a dam between the integral bushing of the sealing fitting and the end of the conduit to keep Chico SpeedSeal Compound contained in sealing fitting while in the liquid state. Simply pack it in the conduit hub. No need to separate conductors.
- not required in horizontal applications, unless user wants to keep Chico SpeedSeal Compound out of conduit, adjacent fittings or enclosures.

- packaged with a screw-on nozzle for accurate dispensing.
- expands four times its original size in the sealing fitting, eliminating the need to separate the individual conductors with Chico X fiber.
- Chico X fiber dams are not required in horizontal applications, reducing installation times.
- completely hardens in 20 minutes, simplifying use for OEMs.

kept above 10°C (50°F) prior to mixing. The sealing fitting must be kept at or above 4°C (40°F) during the 4 to 10 minute expansion / gel time of the compound.

- one year shelf-life.
- patent pending.

Certifications & Compliances:

- Class I, Division 1, Groups C & D.
- Class II, Division 1, Groups E, F & G.
- UL Listed (UL Standard 866).
- cUL Listed to CSA Standard C22.2 No.

Chico SpeedSeal Ordering Information:

<u>Sealing Fitting Catalog Number *</u>	<u>Amount of SpeedSeal material needed per fitting (in ounces)</u>	<u>Suggested SpeedSeal Catalog Number</u>
EYS1, EYS16, EYS11, EYS116 EYD1, EYD16, EYD11, EYD116 EYS2, EYS26, EYS21, EYS216 EYD2, EYD26, EYD21, EYD216 EYSX11, EYDX11	1	CHICO SS2 (2 oz. Cartridge)
EYS3, EYS36, EYS31, EYS316 EYD3, EYD36, EYD31, EYD316 EYSX21, EYDX21	2	CHICO SS2 (2 oz. Cartridge)
EYS41, EYS416, EYS4, EYS46 EYD4, EYD46, EYD41, EYD416 EYS51, EYS516, EYS5, EYS56 EYD5, EYD56, EYD51, EYD516 EYSX31, EYDX31 EYSX41, EYDX41	3	CHICO SS6 (6 oz. Cartridge)
EYS61, EYS616, EYS6, EYS66 EYD6, EYD66, EYD61, EYD616 EYSX51, EYDX51	6	CHICO SS6 (6 oz. Cartridge)

* Chico SpeedSeal Compound will be available for use with EYD drain seals by September 2003.

For more information:

Contact an authorized Cooper Crouse-Hinds Distributor, Sales Office or Customer Service Department:

In the U.S.:

Cooper Crouse-Hinds
P.O. Box 4999
Syracuse, NY 13221
(315) 477-5531
FAX: (315) 477-5179
crouse.customerctr@crouse-hinds.com

In Canada:

Cooper Crouse-Hinds Canada
(905) 507-4187
FAX: (905) 568-7048

For office locations outside of North America or for additional product information, visit our website at: www.crouse-hinds.com



Crouse-Hinds is a registered trademark of Cooper Industries, Inc.
© 2003 Cooper Industries, Inc.

Printed

Chico X Fiber Ordering Information:

<u>Net Weight</u>	<u>Catalog Number</u>
2 oz.	CHICO X4
8 oz.	CHICO X6
1 lb.	CHICO X7

The amount of fiber required is based on the hub size. See following chart:

<u>Hub Size</u>	<u>Fiber required (in ozs.)</u>
1/2"	1/32
3/4"	1/16
1"	1/8
1 1/4"	1/4
1 1/2"	1/2
2"	1

Cooper Ex. 1