

PA 1177621

THE UNITED STATES OF AMERICA**TO ALL TO WHOM THESE PRESENTS SHALL COME:****UNITED STATES DEPARTMENT OF COMMERCE****United States Patent and Trademark Office**

June 01, 2004

REC'D 01 JUL 2004


WIPO PCT


**THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM
THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK
OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT
APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A
FILING DATE UNDER 35 USC 111.**

APPLICATION NUMBER: 60/518,327**FILING DATE: November 10, 2003****PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

**By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS**




P. SWAIN
Certifying Officer

PATENT APPLICATION SERIAL NO. _____

U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICE
FEE RECORD SHEET

11/13/2003 DTESEN1 00000054 60518327

01 FC:2005

80.00 DP

PTO-1556
(5/87)

*U.S. Government Printing Office: 2002 — 489-267/65033

Copy provided by USPTO from the PACR Image Database on 05/28/2004

Please type a plus sign (+) inside this box →

+

PTO/SB/16 (5-03)
Approved for use through 4/30/2003. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.**PROVISIONAL APPLICATION FOR PATENT COVER SHEET**

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c).

INVENTOR(S)						
Given Name (first and middle [if any])		Family Name or Surname		Residence (City and either State or Foreign Country)		
David Mark J.		BAKER MOORE		United Kingdom United Kingdom		
<input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto						
TITLE OF THE INVENTION (280 characters max)						
COMMUNICATIONS SYSTEMS AND METHODS						
Direct all correspondence to: CORRESPONDENCE ADDRESS						
<input checked="" type="checkbox"/> Customer Number		27082			Place Customer Number Bar Code Label here	
OR		Type Customer Number here				
<input checked="" type="checkbox"/> Firm or Individual Name		DORSEY & WHITNEY LLP				
Address		1001 Pennsylvania Avenue, N.W.				
Address		Suite 400 South				
City		Washington		State	DC	ZIP 20004
Country		USA		Telephone	202-442-3000	Fax 202-442-3199
ENCLOSED APPLICATION PARTS (check all that apply)						
<input checked="" type="checkbox"/> Specification		Number of Pages		35		<input type="checkbox"/> CD(s), Number
<input checked="" type="checkbox"/> Drawing(s)		Number of Sheets		15		<input type="checkbox"/> Other (specify)
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76						
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)						
<input checked="" type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.						FILING FEE AMOUNT (\$)
<input checked="" type="checkbox"/> A check or money order is enclosed to cover the filing fees						
<input checked="" type="checkbox"/> The Director is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number		04-1425				\$80.00
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.						
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.						
<input checked="" type="checkbox"/> No.						
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____						

Respectfully submitted,

SIGNATURE

Daniel E. Fisher

Date

11/10/03

TYPED or PRINTED NAME

Daniel E. Fisher

TELEPHONE

202-442-3000

REGISTRATION NO.

34,162

(if appropriate)

Docket Number:

33746P

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop Provisional Application, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

P1MALL/REV05

Communications Systems and Methods

This invention generally relates to networks of communications devices, in particular ultra wideband (UWB) communications devices.

Techniques for UWB communication developed from radar and other military applications, and pioneering work was carried out by Dr G.F. Ross, as described in US3728632. Ultra-wideband communications systems employ very short pulses of electromagnetic radiation (impulses) with short rise and fall times, resulting in a spectrum with a very wide bandwidth. Some systems employ direct excitation of an antenna with such a pulse which then radiates with its characteristic impulse or step response (depending upon the excitation). Such systems are referred to as "carrier free" since the resulting rf emission lacks any well-defined carrier frequency. However other UWB systems radiate one or a few cycles of a high frequency carrier and thus it is possible to define a meaningful centre frequency and/or phase despite the large signal bandwidth. The US Federal Communications Commission (FCC) defines UWB as a -10dB bandwidth of at least 25% of a centre (or average) frequency or a bandwidth of at least 1.5GHz; the US DARPA definition is similar but refers to a -20dB bandwidth. Such formal definitions are useful and clearly differentiates UWB systems from conventional narrow and wideband systems but the techniques described in this specification are not limited to systems falling within this precise definition and may be employed with similar systems employing very short pulses of electromagnetic radiation.

UWB communications systems have a number of advantages over conventional systems. Broadly speaking, the very large bandwidth facilitates very high data rate communications and since pulses of radiation are employed the average transmit power (and also power consumption) may be kept low even though the power in each pulse may be relatively large. Also, since the power in each pulse is spread over a large

bandwidth the power per unit frequency may be very low indeed, allowing UWB systems to coexist with other spectrum users and, in military applications, providing a low probability of intercept. The short pulses also make UWB communications systems relatively unsusceptible to multipath effects since multiple reflections can in general be resolved. Finally UWB systems lend themselves to a substantially all-digital implementation, with consequent cost savings and other advantages.

Figure 1a shows a typical UWB transceiver 100. This comprises an transmit/receive antenna 102 with a characteristic impulse response indicated by bandpass filter (BPF) 104 (although in some instances a bandpass filter may be explicitly included), couples to a transmit/receive switch 106.

The transmit chain comprises an impulse generator 108 modulatable by a baseband transmit data input 110, and an antenna driver 112. The driver may be omitted since only a small output voltage swing is generally required. One of a number of modulation techniques may be employed, typically either OOK (on-off keying i.e. transmitting or not transmitting a pulse), M-ary amplitude shift keying (pulse amplitude modulation), or PPM (pulse position modulation i.e. dithering the pulse position). Typically the transmitted pulse has a duration of $<1\text{ns}$ and may have a bandwidth of the order of gigahertz.

The receive chain typically comprises a low noise amplifier (LNA) and automatic gain control (AGC) stage 114 followed by a correlator or matched filter (MF) 116, matched to the received pulse shape so that it outputs an impulse when presented with rf energy having the correct (matching) pulse shape. The output of MF 116 is generally digitised by an analogue-to-digital convertor (ADC) 118 and then presented to a (digital or software-based) variable gain threshold circuit 120, the output of which comprises the received data. The skilled person will understand that forward error correction (FEC) such as block error coding and other baseband processing may also be employed, but such techniques are well-known and conventional and hence these is omitted for clarity.

Figure 1b shows one example of a carrier-based UWB transmitter 122, as described in more detail in US 6,026,125 (hereby incorporated by reference). This form of

Explore Litigation Insights

Docket Alarm provides insights to develop a more informed litigation strategy and the peace of mind of knowing you're on top of things.

Real-Time Litigation Alerts



Keep your litigation team up-to-date with **real-time alerts** and advanced team management tools built for the enterprise, all while greatly reducing PACER spend.

Our comprehensive service means we can handle Federal, State, and Administrative courts across the country.

Advanced Docket Research



With over 230 million records, Docket Alarm's cloud-native docket research platform finds what other services can't. Coverage includes Federal, State, plus PTAB, TTAB, ITC and NLRB decisions, all in one place.

Identify arguments that have been successful in the past with full text, pinpoint searching. Link to case law cited within any court document via Fastcase.

Analytics At Your Fingertips



Learn what happened the last time a particular judge, opposing counsel or company faced cases similar to yours.

Advanced out-of-the-box PTAB and TTAB analytics are always at your fingertips.

API

Docket Alarm offers a powerful API (application programming interface) to developers that want to integrate case filings into their apps.

LAW FIRMS

Build custom dashboards for your attorneys and clients with live data direct from the court.

Automate many repetitive legal tasks like conflict checks, document management, and marketing.

FINANCIAL INSTITUTIONS

Litigation and bankruptcy checks for companies and debtors.

E-DISCOVERY AND LEGAL VENDORS

Sync your system to PACER to automate legal marketing.